



Figs. 1369 - 1374 Series Lights

Certified For Use on Vessels Over 20 Meters (65.6 ft.) in Length

CONSTRUCTION:

- Lightweight But Durable Fiber-Filled Black Polymer
 - Pre-Wired Medium Prefocus Socket
- Includes One 3 Foot Length of 16/2-SO Cable Through Watertight Terminal Tubes
- Watertight Access Cap for Rebulbing and Cleaning
 - Rough Service Bulbs are Available

Ordering Info				
Description	Visibility Arc	Visibility Miles	Std. Pkg. 1 Pc.	Ship Wt. Carton Lbs. Standard Pkg.
Red Side Light	112-1/2°	3	1372RE0BLK	4.4
Green Side Light	112-1/2°	3	1372GE0BLK	4.4
White Masthead Light	225°	6	1373E00BLK	4.3
White Stern Light*	135°	3	1374E00BLK	4.4
Yellow Towing Light	135°	3	1374ME0BLK	4.4
White All-Round Light*	360°	3	1369E00BLK	4.1
White All-Round Light**	360°	6	1369HE0BLK	4.1
Red All-Round Light	360°	3	1370RE0BLK	4.1
Green All-Round Light	360°	3	1370GE0BLK	4.1
Yellow All-Round Light	360°	3	1370ME0BLK	4.1

Tech Info
Bulb: 24, 120 or 220 Volt (Not Included, see below)
Mounting Bolt Size: 3/8"
Height Overall: 9-1/4"
Height Lens: 6-3/4"

Special lights to meet local requirements are available upon request.
 *These lights are supplied with a Gray Tinted Lens
 **For Great Lakes use

Fig. 1372
Green Side Light



Fig. 1370
Green All-Round



Fig. 1370
Red All-Round



Fig. 1372
Red Side Light



Fig. 1373
White Masthead



Fig. 1370
Yellow All-Round



Fig. 1374
White Stern

IMPORTANT BULB DATA
 To comply with UL Standard A-1104 (A.B.Y.C.), the lights listed on this page must be used with the following PERKO bulbs:
 24 Volt Use Cat. No. 0342024CLR
 120 Volt Use Cat. No. 0342004CLR or 0342RS4CLR when a "Rough Service" bulb is required.
 220 Volt Use Cat. No. 0342220CLR.

SPARE PARTS ORDERING INFORMATION
 Access Cap Assembly: 1363SGLBLK
 Medium Prefocus Socket: 0367
 Bulb Information:
 24V = 0342024CLR
 120V = 0342004CLR or 0342RS4CLR
 220V = 0342220CLR

See Page C-36 for Bulb Information.