



Figs. 1164 - 1168 Series Lights

Certified For Use on Vessels Over 20 Meters (65.6 ft.) in Length

CONSTRUCTION:

- Heavy Duty Cast Bronze
- Pre-Wired Medium Prefocus Socket in Each Compartment
- Two 3 Foot Lengths of 16/3-SO Cable Through a Watertight Terminal Tube
- Watertight Access Cap for Rebulbing and Cleaning
- 120 Volt Only, Bulb Not Included
- Rough Service Bulbs are Available



| Ordering Info | | | | Tech Info | |
|-------------------------|----------------|------------------|-----------------|------------------------------------|--|
| Description | Visibility Arc | Visibility Miles | Std. Pkg. 1 Pc. | Ship Wt. Carton Lbs. Standard Pkg. | |
| Red Side Light | 112-1/2° | 3 | 1164RE0PLB | 22.5 | Bulb: 120 Volt (Not Included) 0342004CLR or 0342RS4CLR Mounting Bolt Size: 3/8" Height Overall: 17-1/4" Height Lens: 6-3/4" |
| Green Side Light | 112-1/2° | 3 | 1164GE0PLB | 22.5 | |
| White Masthead Light | 225° | 6 | 1165E00PLB | 21.5 | |
| White Stern Light* | 135° | 3 | 1166E00PLB | 22.3 | |
| Yellow Towing Light | 135° | 3 | 1166ME0PLB | 22.4 | |
| White All-Round Light* | 360° | 3 | 1167E00PLB | 20.0 | |
| White All-Round Light** | 360° | 6 | 1167HE0PLB | 20.0 | |
| Red All-Round Light | 360° | 3 | 1168RE0PLB | 20.0 | |
| Green All-Round Light | 360° | 3 | 1168GE0PLB | 20.0 | |
| Yellow All-Round Light | 360° | 3 | 1168ME0PLB | 20.0 | |

Special lights to meet local requirements are available upon request

*These lights are supplied with a Gray Tinted Lens

**For Great Lakes use



Fig. 1164
Green Side Light



Fig. 1168
Red All-Round



Fig. 1166
Yellow Towing



Fig. 1167
White All-Round



Fig. 1164
Red Side Light

Spare Parts Ordering Information

Spare Lenses:
Red: 0261001RED
Green: 0261001GRN
White: 0261001CLR
Gray: 0261001GRY
Yellow: 0261001YLW

Lens Gasket: 1143
O-Ring for Cap: 1119
Dual Medium Prefocus Socket Assembly: 0303
Lens Retaining Clip with Bolt: 1133
Access Cap, O-Ring and Retainer: 1105000BLK



IMPORTANT BULB DATA
To comply with UL Standard A-1104 (A.B.Y.C.), the lights listed on this page must use a PERKO Cat. No. 0342004CLR bulb or 0342RS4CLR bulb when a "Rough Service" bulb is required.

See Page C-36 for Bulb Information.