



## Figs. 1150 - 1153 Series Navigation Lights

Certified For Use on Vessel Lengths as Specified Below

### CONSTRUCTION:

- Sheet Metal, Preprimed Galvanized Steel
  - Medium Prefocus Socket
- Watertight Terminal Tube for 16/3-SO Cable
- Watertight Access Cap for Rebulbing and Cleaning

Ordering Info					
Certified For Use on Vessels 20 Meters (65.6 ft.) to 50 Meters (164.0 ft.) in Length					
Description	Standard Pkg. 1 Pc.	Visibility Arc	Visibility Miles	Required Bulb	Ship Wt. Carton Lbs. Std. Pkg.
Red Side Light	1150RE1GAL	112-1/2°	2	0342002CLR	6.1
Green Side Light	1150GE1GAL	112-1/2°	2	0342002CLR	6.1
White Masthead Light	1151E01GAL	225°	5	0342003CLR	6.3
White Stern Light	1152E01GAL	135°	2	0342000CLR	6.1
Yellow Towing Light	1152ME1GAL	135°	2	0342000CLR	6.1
White All-Round Light	Discontinued - See Fig. 1153E02GAL Below				
Certified For Use on Vessels Over 20 Meters (65.6 ft.) in Length					
Red Side Light	1150RE2GAL	112-1/2°	3	0342004CLR*	10.9
Green Side Light	1150GE2GAL	112-1/2°	3	0342004CLR*	10.9
White Masthead Light	1151E02GAL	225°	6	0342004CLR*	10.0
White Stern Light	1152E02GAL	135°	3	0342002CLR	9.5
White All-Round Light	1153E02GAL	360°	3	0342003CLR	10.6

Tech Info
Bulb: 120 Volt (Not Included)
Screw Size: 1/4" <b>Size No. 1</b>
Height Overall: 11-1/2"
Height Lens: 6-3/4" <b>Size No. 2</b>
Height Overall: 13-1/2"
Height Lens: 7-1/2"

\*0342RS4CLR bulbs can be substituted for 0342004CLR where "Rough Service" bulbs are required



Fig. 1150                      Fig. 1151                      Fig. 1152                      Fig. 1153

### SPARE PARTS ORDERING INFORMATION (ALSO SEE PAGE C-36)

Lenses:

- 112-1/2°    0259 No. 1 or 2, Specify RED or GRN.
- 135°        0269 No. 1 or 2, Specify YLW or WHT.
- 225°        0256 No. 1 or 2, WHT.
- 360°        0261F No. 1 or 2, Specify RED, GRN, YLW or WHT.

- Medium Prefocus Socket: 0347A00.
- Access Cap, O-Ring and Retainer: 1105000BLK.
- O-Ring for Cap: 1119.
- Socket Supports: 0341001PLB or 034101APLB.

**IMPORTANT BULB DATA**  
 To comply with UL Standard A-1104 (A.B.Y.C.), the lights listed as specified above on this page must use a PERKO Cat. No. 0342 bulb, as specified above.

See Page C-36 for Bulb Information.