

## Horizontal Mount Bi-Color Lights

### 2-mile (USCG 2nm) Certified

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Zinc Alloy Top with Polymer Base,  
 Finish: Chrome Plated or White Powder Coated  
 Dimensions: Length: 3-1/4", Width: 2-1/4", Height: 1-1/2"  
 Screw Size: #6  
 Contacts: Gold Plated  
 Voltage: 12V (Bulb Included)  
 Wattage: 10 watts  
 Amperage: .80 amps



Fig. 0227 Chrome

White

Finish	Retail Pkg.	OEM Bulk Pkg.
Chrome	0227DP0CHR	0227000CHR
White	0227DP0WHT	0227000WHT



Navigation Lights

2

### 1-mile (USCG 1nm) Certified - Patent No. 4,500,947

Use on Power Driven Vessels Under 12m (39.4 ft.) in Length

Material: Zinc Alloy Top, Black Polymer Base  
 Finish: Chrome Plated  
 Dimensions: Length: 4", Width: 3-1/8", Height: 1-7/8"  
 Screw Size: #8  
 Contacts: Gold Plated  
 Voltage: 12V (Bulb Included)  
 Wattage: 10 watts  
 Amperage: .80 amps



Fig. 1310

Finish	Retail Pkg.	OEM Bulk Pkg.
Chrome	1310DP0CHR	1310000CHR



### 1-mile (USCG 1nm) Certified

Use on Sail or Power Driven Vessels Under 12m (39.4 ft.) in Length

Material: Brass or Stainless Steel Top, Polymer Base  
 Finish: Chrome Plated or Polished  
 Dimensions: O.D. Base: 2-3/8", Height: 1-5/8"  
 Screw Size: #4  
 Contacts: Gold Plated  
 Voltage: 12V (Bulb Included)  
 Wattage: 10 watts  
 Amperage: .80 amps

Fig. 0972



Finish	Retail Pkg.	OEM Bulk Pkg.
Chrome	0972DP0CHR	0972000CHR
Polished SS	0972DP0STS	0972000STS



Note: The above lights can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. Replace the bulbs provided with Cat. No. 0072DP1CLR 24-volt bulbs.

Contact us for 24-volt applications on new construction.

**Fig. 0227:**  
 Bulbs: 0071DP0CLR.  
 Lens: 0227DP0LNS.  
 Black Base w/Socket Assy: 022700099A.  
 White Base w/Socket Assy: 0227W0099A.  
**Fig. 0972:**  
 Bulbs: 0071DP0CLR.  
 Base with Socket Assembly: 0135.  
 Lens, Old Style Open Top: 0296DP0LNS.  
 New Style Closed Top: 0297DP0LNS.

#### Spare Parts Information



Fig. 0227DP0LNS

**Fig. 1310:**  
 Bulbs: 0071DP0CLR.  
 Lens: 0283DPALNS.  
 Base w/Socket Assy: 0136.



Fig. 0283DPALNS



Fig. 0296DP0LNS



Fig. 0297DP0LNS



Fig. 0071 DP0CLR