

Navigation Light Sets

2 Mile/3 Mile Certified (USCG 2nm/3nm)

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Polymer
 Finish: Black
 Dimensions: Fig 0109:
 H: 5-1/4", W: 5-1/2", Proj: 3-7/8"
 Lens Height: 4-1/4"
 Figs 0110 & 0111:
 H: 5-1/4", W: 4-3/4", Proj: 3-7/8"
 Screw Size: #10
 Voltage: 12 or 24V (Bulb Not Included)
 12V 24V
 Wattage: 15 watts 18 watts
 Amperage: .97 amps .75 amps



CE

Fig. 0110 Masthead



Fig. 0109 Side Lights

Fig. 0111 Stern & Towing

Std. Pkg.	Description	Visibility Arc	Visibility Miles
0109R00BLK	Red Side Light	112-1/2°	2nm
0109G00BLK	Green Side Light	112-1/2°	2nm
0110000BLK	White Masthead Light	225°	3nm
0111000BLK	White Stern Light	135°	2nm
0111M00BLK	Yellow Towing Light	135°	2nm

2 Mile (USCG 2nm) Certified

Use on Power Driven Vessels Under 20m (65.6 ft.) in Length

Material: Polymer
 Finish: Black Base, White, Red, or Green Lens
 Dimensions: Height: 6", O.D. Base: 3-1/8", Lens Height: 5"
 Tapped Pipe Size: 1/2"
 Screw Size: #10
 Voltage: 12, 24 or 32 Volt (Bulb Not Included)
 12V 24V
 Wattage: 15 watts 18 watts
 Amperage: .97 amps .75 amps



Fig. 0108 White

Pipe Mount Base



Green

Red

Std. Pkg.	Description	Visibility Arc	Visibility Miles
0108000BLK	White All-Round Light*	360°	2nm
0108R00BLK	Red All-Round Light	360°	2nm
0108G00BLK	Green All-Round Light	360°	2nm

*This Light is Supplied with a Gray Tinted Globe.

Spare Parts Information

Replacement Lenses:

112-1/2° Fig. No. 0259H02, Specify RED or GRN.
 135° Fig. No. 0269H02, Specify YLW or WHT.
 225° Fig. No. 0256H02WHT.
 360° Fig. No. 0106000, Specify RED, GRN, GRY or WHT.

Lens Dimensions

Fig. 0259: 4-1/4" x 4"
 Fig. 0269: 4-1/4" x 4"
 Fig. 0256: 4-1/4" X 4-1/4"
 Fig. 0106: 5" X 3-5/8" O.D.

Required Bulbs:

For 12 Volt: 0070DP1CLR.
 For 24 Volt: 0067DP2CLR.
 For 32 Volt: 0070DP2CLR.
 Base and Gasket for Fig. No. 0108: 0222DP0BLK.

