

Cockpit Utility Lights

Reduced Glare Clear Back Utility Light

The clear back allows light to shine both inside and outside of the mounting location


- Material: Brass or Stainless Steel with Clear Polymer Back
 Finish: Chrome Plated or Polished
 Dimensions: O.D.: 3", Depth: 1"
 Installs In: 2-1/8" Diameter Hole
 Screw Size: #8
 Voltage: 12V (Bulb included), 24V with bulb change
 Wattage: 10 watts
 Amperage: .83 amps
 Features:
 - Directs 80% of the light downward, thus reducing cockpit glare.
 - Ideal for mounting on center consoles, storage lockers, cabinets, and electronics boxes.



Fig. 1149

Finish	Retail Pkg.	OEM Bulk Pkg.
Chrome	1149DP112V	114900112V
Polished SS	1149DP1STS	1149001STS

Diagram of center console mt.



Reduced Glare Design Cockpit Light

Directs 80% of the Light Downward, Thus Reducing Cockpit Glare

- Material: Brass, Stainless Steel, or Polymer with Polymer Base
 Finish: Chrome Plated, Polished, or White
 Dimensions: O.D.: 3", Depth: 1"
 Installs In: 2-1/8" Diameter Hole
 Screw Size: #8
 Voltage: 12V (Bulb included), 24V with bulb change
 Wattage: 10 watts
 Amperage: .74 amps



Fig. 1146 Chrome

Finish	Voltage	Retail Pkg.	OEM Bulk Pkg.
Chrome	12	1146DP112V	114600112V
Chrome	24	1146DP224V	114600224V
Polished SS	12	1146DP1STS	1146001STS
Polished SS	24	1146DP2STS	1146002STS
White	12	1146DP1WHT	1146001WHT
White	24	1146DP2WHT	1146002WHT



Stainless



White



Low Profile LED Ceiling Mount Utility Lights

- Material: Brass, Stainless Steel, or White PERKO•Kote with Polymer Base
 Finish: Chrome Plated, Polished, or White
 Dimensions: O.D.: 3"
 Installs In: 2-1/8" Diameter Hole
 Screw Size: #8
 Voltage: 12V LED
 Wattage: 4.5 watts
 Amperage: 0.3 amps
 Features: Uses less than half the energy draw of standard lights.



Fig. 1156 Chrome

Finish	Retail Pkg.	OEM Bulk Pkg.
Chrome	1156DP112V	115600112V
Polished SS	1156DP1STS	1156001STS
White	1156DP1WHT	1156001WHT

Low profile side view



Fig. 1149:

Socket Assy: 114900099B.
 Lens w/Gasket: 1146DP099A.
 Mounting Flange: 094600099C

Fig. 1146:

Socket Assy: 114600099B.
 Lens w/Gasket: 1146DP099A.
 Mounting Flange: 094600099C

Spare Parts Information



Fig. 1146 & 1149 Bulbs:

12 Volt Bulbs: 0070DP0CLR.
 24 Volt Bulbs: 0067DP1CLR.