



Higher Capacity Intake Water Strainer

Intake Water Strainers

Material: For Pipe Sizes: Use:	Cast Bronze, Stainless Steel Basket and Clear Polycarbonate Cylinder 2", 2-1/2", and 3" NPT For Applications requiring Higher Capacity
Features:	 Designed for easy installation and cleaning Mounting lugs cast into both sides to assure universal mounting Four outside tie rods Stainless steel strainer basket minimizes electrolysis 0.079" Screen hole diameter provides 47% open area, among the highest in the industry for cylindrical strainer baskets. Hinged lugs on cover permit easy removal and cleaning of the strainer basket A drain plug in the bottom casting for easily removing sediment and draining for winterizing

FIG. 0500 - DIFFERENTIAL PRESSURE GRAPHS

125 150 Flow GPM





Pipe Size	Height Overall	Width Overall	Standard Pkg.	Dimensions Cylinder	Dimensions Basket	Open Area To Pipe Size Ratio	Spare Gasket Kit* Retail Pkg.
2″	14-1/2″	9″	0500009PLB	8" x 10"	3-7/8" x 10-1/4"	20:1	0500DP999M (or) 99R
2-1/2″	16-1/2″	9″	0500010PLB	8″ x 12″	3-7/8″ x 12-1/4″	18:1	0500DP999M (or) 99R
3″	18-1/2″	9″	0500011PLB	8″ x 14″	3-7/8" x 14-1/4"	14:1	0500DP999M (or) 99R

Fig. 0500

(Sizes 2"

175

*Spare Gasket Kit Consists of: 1 Cover Gasket and 2 Cylinder Gaskets

Visit <u>www.perko.com</u> for installation instructions and technical drawings on most PERKO° products.

D r o p